



AMBULANCE



ENGINE	
Type	3.0L 4 Cylinder ZD30 CRS Diesel
Displacement	2953 cc
Power	118 ps @ 2750 rpm
Torque	320 Nm @ 1500-2400 rpm
Emission	Euro III / Euro IV

GEARBOX	
Type	5 Speed synchromesh

FRAME	
Туре	C in C frame with Outrigger arrangement

BRAKES	
Туре	Vacuum assisted hydraulic drum brake

TYRES	
Туре	Single tyre – Radial 7.5R16 (for Mini Bus)
	Rear Twin tire – Radial 7R16 (for Midi Bus)

GVW 4420/5800 kg (Mini / Midi)
--

SEATING	
Tuno	2X1 Mini Bus
Type	2X2 Midi Bus

DIMENSIONS	
Overall Length	5615/6980 mm
Overall Width	2060 mm
Overall Height	2630 mm
Wheelbase	3100/3700 mm
Front Track	1562/1612 mm
Rear Track	1540/1480 mm
Front Overhang	1060 mm
Rear Overhang	1455/2220 mm
Ground Clearance	198 mm
Turning Circle	
Radius	8.2 m

SUSPENSION	
Туре	Parabolic, overslung suspension with Double acting Shock Absorber



Body Structure	Combination of MS Tubular & Press Sections phosphatised. C/B channel ISMC 75,
Paneling	External Paneling – 20SWG/GI, Interior Paneling – 24 Swg GI sheets
	at roof and SS thrust panels .
Front Show	As supplied with chassis (Original)with Twin W/S glass
Floor	2mm Vinyl mat on 10mm Th. plywood.
NAC	1/3 Fix, 2/3 Sliding toughened Tinted flat glasses in powder coated
Windows	aluminum frame .
Driver & Co-Driver Door	Hinge Type half flap door with lock with sliding window glass.
City C Book Book	Flap doors with sliding window glass, lock & handle at rear and one
Side & Read Door	JK door at RH side.
Partition	Full partition with communication window.
Battery Box	At suitable place, fabricated out of MS sheet
	SS Medical Cabinet cum Doctor`s table with wash basin and
	25 lit water tank.
	Drinking water jug 20 lit.
	Revolving Chair.
	Stretcher cum seat 1 No.
Salaan Campanturanta with	Stretcher Trolley 1 No.
Saloon Compartments with	Foldable Stretcher 2 Nos.
	Oxygen cylinder bracket 2 Nos.
	Oxygen supply system.
	 Soap container, Towel holder, dust Bin.
	Saline water bottle hooks 2 Nos.
	Curtain 1 No.
	Provision for Curtain at windows.
Sun visor	For driver and co-driver - folding type
Rear view Mirror	Exterior on both sides and interior in driver's area
Roof Lamp	One for driver & three for saloon area,
	Fluorescent lamp, spot lamps. Original tail lamps repositioned at
Electrical	rear, Light Bar with Siren and integrated public addressing system of
Electrical	100W, Inverter 600watts/800VA Flood lights, Marker Lights 4 nos
	Coach Fan.
Paint	High gloss finish quick drying type PU base paint. (Standard colour
	scheme: As per your colour choice.
Bumper	Bumpers at rear, Front as supplied with chassis
Seating	Driver & Co-driver seats with seat
Fitments	One Fire Extinguisher dry powder type (1 Kg), First Aid box with
	medicine, Drinking Water container.
Ĺ	<u> </u>